

Application No. 10/049,245
Amendment dated May 17, 2006
Reply to Office action dated February 22, 2006

Page 3 of 17

48. (previously presented) A method according to claim 47, wherein the substrate-supported membrane is a fluid lipid membrane, particularly comprising at least one of the lipids activated by PEG and DAC-Chol lipids.

49. (previously presented) A method according to claim 48, wherein the fluid lipid membrane is a cationic fluid lipid membrane.

50. (previously presented) A method according to claim 48, wherein the fluid lipid membrane includes amphiphilic macromolecules.

51. (previously presented) A method according to claim 48, wherein the fluid lipid membrane includes bilayers of charged lipids.

52. (previously presented) A method according to claim 47, wherein the electrical field is a pulsed electrical field.

53. (previously presented) A method according to claim 47, wherein the electrical field is an alternating field on which a time constant field is superimposed.

54. (previously presented) A method according to claim 53, wherein the alternating field and the time constant field are superimposed in a crosswise manner.

Application No. 10/049,245
Amendment dated May 17, 2006
Reply to Office action dated February 22, 2006

Page 4 of 17

55. (previously presented) A method according to claim 47, wherein the structured membrane-compatible surface including ribs, supporting the membrane.

56. (previously presented) A method according to claim 55, wherein the substrate exhibits a periodicity ranging from 2 nm to 200 nm.

57. (previously presented) A method according to claim 55, wherein the ribs have a height in the range of 1 nm to 10 nm.

58. (previously presented) A method according to claim 55, wherein the electrical field is a time constant field having a direction that is substantially parallel to the ribs.

59. (previously presented) A method according to claim 47, wherein said movement is a rotation.

60. (previously presented) A method according to claim 47, wherein:
the substrate includes an exclusion area in which the particles are not mobile; and
the method further comprises collecting the particles at said exclusion area upon providing the electrical field, prior to performing the electrophoresis.

61. (previously presented) A method according to claim 60, wherein:

Application No. 10/049,245
Amendment dated May 17, 2006
Reply to Office action dated February 22, 2006

Page 5 of 17

the substrate-supported membrane is a fluid lipid membrane, particularly comprising at least one of the lipids activated by PEG and DAC-Chol lipids; and the exclusion area is a non-fluid area of the fluid lipid membrane.

62. (previously presented) A method of observing an electrophoretic separation, comprising:

performing the method for the electrophoretic separation of particles of claim 47;
recording digitized image data of the electrophoretic movement; and
evaluating the recorded image data using a computer.

63. (previously presented) A method according to claim 47, wherein the particles to be separated include at least one of DNA, RNA, DNA-oligomers, RNA-oligomers, and proteins.

64. (previously presented) A method according to claim 47, further comprising providing a pH gradient, wherein the particles migrate according to the pH gradient.

65. (previously presented) A method according to claim 64, wherein the pH gradient is provided parallel to the electrical field.

66. (previously presented) A method according to claim 64, wherein the pH gradient is provided substantially perpendicular to the electrical field.

Application No. 10/049,245
Amendment dated May 17, 2006
Reply to Office action dated February 22, 2006

Page 6 of 17

67. (currently amended) A method of providing a microchannel electrophoresis chamber, comprising:

providing at least one channel having a bottom surface including a substrate-supported membrane, wherein the substrate-supported membrane ~~comprising:~~ includes a substrate and a dried-up fluid lipid membrane, wherein the dried-up fluid lipid membrane is composed only of lipids swelled from a dried up lipids, and

reconstituting the dried-up fluid lipid membrane by swelling lipids in the membrane state by the addition of only one or more fluid selected from the group consisting of at least one of water and a buffer solution.

68. (currently amended) ~~A microchannel electrophoresis chamber~~ The method according to claim 67, wherein the dried-up fluid lipid membrane includes cationic lipids.

69. (currently amended) ~~A microchannel electrophoresis chamber~~ The method according to claim 67, ~~wherein the fluid lipid membrane includes~~ further comprising adding amphiphilic macromolecules to the dried-up fluid lipid membrane, prior to reconstituting the dried-up fluid lipid membrane.

70. (currently amended) ~~A microchannel electrophoresis chamber~~ The method according to claim 67, wherein the dried-up fluid lipid membrane includes bilayers of charged lipids.

Application No. 10/049,245
Amendment dated May 17, 2006
Reply to Office action dated February 22, 2006

Page 7 of 17

71. (currently amended) ~~A microchannel electrophoresis chamber~~ The method according to claim 67, wherein the dried-up fluid lipid membrane includes at least one non-fluid area.

72. (currently amended) ~~A microchannel electrophoresis chamber~~ The method according to claim 67, wherein the substrate includes an optically transparent material.

73. (currently amended) ~~A microchannel electrophoresis chamber~~ The method according to claim 72, wherein the optically transparent material includes plastic.

74. (currently amended) ~~A microchannel electrophoresis chamber~~ The method according to claim 73, wherein the plastic includes at least one of PC, PMMA, PS, PE, and plastic formed of cyclic olefins.

75. (currently amended) ~~A microchannel electrophoresis chamber~~ The method according to claim 72, wherein the optically transparent material includes glass.

76. (currently amended) ~~A microchannel electrophoresis chamber~~ The method according to claim 67, further comprising connecting an electrode assembly ~~connected~~ to the channel.

Application No. 10/049,245

Page 8 of 17

Amendment dated May 17, 2006

Reply to Office action dated February 22, 2006

77. (currently amended) ~~A microchannel electrophoresis chamber~~ The method according to claim 76, wherein each channel has a width ranging from 1 μm to 10 μm .

78. (currently amended) ~~A microchannel electrophoresis chamber~~ The method according to claim 76, wherein each channel has a depth ranging from 10 nm to 20 μm .

79. (currently amended) ~~A microchannel electrophoresis chamber~~ The method according to claim 76, wherein the at least one channel is a plurality of channels arranged as a two-dimensional matrix.

80. (currently amended) ~~A microchannel electrophoresis chamber~~ The method according to claim 76, wherein the electrode assembly includes an electrode disposed at each longitudinal end of each said channel.

81. (currently amended) ~~A microchannel electrophoresis chamber~~ The method according to claim 76, wherein the electrode assembly includes an electrode extending longitudinally in the direction of the channel at each side of each channel.

82. (canceled)

83. (canceled)

Application No. 10/049,245
Amendment dated May 17, 2006
Reply to Office action dated February 22, 2006

Page 9 of 17

84. (canceled)